## **CLAIMS:**

- 1. A razor having an elongate handle body adapted at a bottom end for attachment to a shaving head, the handle body having a body cavity for receiving a trimming wand, and a trimming wand adapted to be concealed in said cavity and to be selectively withdrawn from the cavity, the trimming wand having at least one trim blade at one end.
- 2. A razor according to Claim 1 in which the handle body has means for releasably coupling the body to a blade cartridge.
- 3. A razor according to Claim 1 in which the shaving head is fixed to the handle body.
- 4. A razor according to Claim 1 in which the handle body is hollow and has an open end opposite said bottom end, the trimming wand being adapted to be slidably received in the said handle body between a stored position in which the trimming wand is concealed by the handle body a retracted position in which the trimming wand is exposed.
- 5. A razor according to Claim 4 in which the handle body has an end cap to seal the open end.
- 6. A razor according to Claim 4 in which the handle body has a slot guide communicating between said cavity and an exterior surface of the handle body and extending along a portion of the handle body between said bottom end and said open end, the trimming wand having a knob extending transversely through said slot at a bottom end of the wand and slidable in said slot.
- 7. A razor according to Claim 1 in which the handle body is hollow and has an open end opposite said bottom end exposing one side of the body cavity, the trimming wand being pivotably coupled to the open end of the handle body between a stored position in which the trimming wand is received in said body cavity to be concealed by the handle body and a flipped position in which the trimming wand is exposed.
- 8. A razor according to Claim 1 in which the handle body is formed in two complimentary body portions separable from each other, one said body portion having said body cavity and the other said boy portion having said trimming wand extending outwardly therefrom along the length

thereof and adapted to be slidably received in said body cavity so that the trimming wand may be concealed in said cavity by the handle body and selectively removed therefrom.